Product Information Sheet

trol gear, light-

control

ing

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources		, , ,	· ·	5, 5		
Supplier's name	e or trade mark:	Sunwind LED 1				
Supplier's address: Logistics Manager, Rudssletta 71, 1351 Rud, NO						
Model identifie	r: 243295,24328	5,243219,243263,5	40981,540983			
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		lamp				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para	meters			
Parameter		Value	Parameter	Value		
		General product p	arameters:			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	Е		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		120 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), ex- pressed in W		1,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	92		
Outer dimen-	Height	115	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con-	Depth	60	range 250 nm to 800			

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-				
		Chromaticity coordi-	0,463				
		nates (x and y)	0,420				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	62	Survival factor	1,00				
the lumen maintenance factor	0,96						

(a)'-': not applicable; (b)'-': not applicable;

